

Amendments to the Specification:

On page 1, please replace the title, with the following amended title:

Title: Improved Frame Assembly for Windows or Doors with Removable Sash

Please replace paragraph [0039], with the following amended paragraph:

[0039] Figure 20 is a front elevation view of the frame assembly shown in Figure [[71]] 17, with the sash frame in the closed position;

Please replace paragraph [0042], with the following amended paragraph:

[0042] Figure 21b is a perspective view of a lower portion of the sash frame shown in Figure [[2]] 18.

Please replace paragraph [0083], with the following amended paragraph:

[0083] In the first portion 118a of the sill 118, screen-mounting details 170a can also be provided. In the embodiment illustrated, the screen mounting details 170a include a screen support step 170, providing in a generally vertical plane an abutment surface 171 against which the frame 174 of a screen 129 can be positioned. The screen mounting details 170a further include horizontal support surfaces 172 provided adjacent the vertical face 171, to support the screen 129 vertically.

Please replace paragraph [0119], with the following amended paragraph:

[0119] The reversible frame assembly 110' has a modified master frame 112' and a modified sash frame 114'. The modified master frame [[112]] 112' has a modified sill 118' which is substantially a mirror image of the header 116. In particular, the sill 118' is provided with the same interlacing configuration 202 as provided in the header 116, thereby defining a second lift position 204' along the

adjacent horizontal elements 118' and 134' of the master frame 112' and sash frame 114', respectively.